

MANUFACTURER: BYD LITHIUM BATTERY CO., LTD

Material Safety Data Sheet

Sect	ion 1 – Product and Com	pany Identificati	on
MANUFACTURER: BYD LITHIUM BATTERY CO., LTD	Product name: Lithium-ion Battery (LiFePO ₄ Battery U3A1-50P-A)		
Address: No.1,Baoping Road, Baolong Industrial Town, Longgang Shenzhen, China	Telephone Number: +86-755-8988 8888 ext.55274 Emergency Telephone Number: +86-755-8988 8888 ext.55274 Fax Number: +86-755-8420 2222 E-mail: www.byd.com.cn		
Prior Notice of Usage	You are kindly requested to use the battery which is delivered from BYD COMPANY LIMITED in strict accordance with the specification and remarks include at the end of the document. Due to improper usage of the battery, an accident or a fire may occur due to the battery generating heat, catching fire or rupture, smoke.		
	Section 2 - Hazard Id	entification	
and storage conditions. the battery to avoid inh	lithium ion battery is norm If a lithium ion battery gen aling internal materials. Ch ome toxicity and it may cau Inhalation, Ingestion, Sk	erates abnormal he emicals which are o se irritation.	at, leave away from
Eye			ation
Skin	The spilliable electrolyte can cause eye irritation. The spilliable electrolyte can cause skin irritation.		
Environment hazards	Do not throw out it into the environment.		
Explosion hazards	May explode in a fire.		
Section	n 3 – Composition/Infor	mation on ingred	ients
Hazardous components	i	CAS#	% (by weight)
LiFePO ₄		15365-14-7	20-30
PVDF		24937-79-9	1.0-1.6
Carbon		7440-44-0	10-18
PTFE			0.2-0.9
Electrolyte		21324-40-3	15-25
PP 2.0-3.6			2.0-3.6
Copper 7440-50-8 8-16			8-16
Aluminum 7429-90-5 12-20			12-20
Steel 15-25			
	Section 4 – First Aid	Measures	

Remove contaminated clothes and shoes immediately. Wash the

Skin contact

	adherence or contact region with soap and plenty of water. Seek medical attention immediately.
Eye contact	Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.
Inhalation	Cover the victim in a blanket, move to the place of fresh air and keep quiet. Seek medical attention immediately. When dyspnea (breathing difficulty) or asphyxia (breath-bald), give artificial respiration immediately.
Ingestion	Get medical aid. Do not induce vomiting. Get medical attention immediately.
	Section 5 – Fire Fighting Measures
Types of hazard	May explode in a fire.
Fire-fighting measures	Although a battery cell is not flammability, in case of fire, move it to the safe place quickly. The following measures are taken when it cannot be moved: Suitable extinguishing media: Dry sand, chemical power fire extinguishing medium. Special hazards: Acrid or harmful fume is emitted during fire. Special protective equipment for firefighters: Protective equipment written in section 8.
Special Information	In the event of a fire, wear full protective clothing and self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.
	Section 6 – Accidental Release Measures
General Information	Use proper personal protective equipment as indicated in section 8.
Spills/Leaks	Internal cell materials, such as electrolyte leaked from battery cell are carefully deals with according to the followings. Personal precaution: Forbid unauthorized person to enter. Remove leaked materials with protective equipment noted in Section 8. Environmental precautions: Do not throw out into the environment. Method of cleaning up: Dilute the leaked electrolyte with water and neutralize with diluted suffuric acid. The leaked solid is moved to a container. The leaked place is fully flushed with water.
	Section 7 – Handling and Storage
Handling	Technical measures: Prevention of user exposure; Not necessary under normal use. Prevention of fire and explosion: Not necessary under normal

r			
	use.		
Precaution for sa			
		image or remove the external shell.	
	Specific safe handling advice:		
	Never throw out battery in a fire or expose to high		
	temperatures.		
	Do not soak battery in water and seawater.		
	Do not expose to strong oxidizers.		
	Do not give a strong mechanical shock or throw down. Never		
	disassemble, modify or deform.		
		t the positive terminal to the negative terminal with	
	electrically conductive material. In the case of charging, use only		
		ge or charge according to the conditions specified by	
	the supplier.		
	Storage condition	ons (suitable to be avoided)	
		ect sunlight, high temperature, high humidity.	
	Store in cool place (temperature: -20~45°C,humidity: 45~		
	85%).		
Storage	Incompatible products		
	Conductive materials, water, seawater, strong oxidizers and		
	strong acids.		
		l (recommended, not suitable)	
Insulative and to		d tear-proof, waterproof materials are recommended.	
		re Controls and Person Protection.	
Occupational exposure limits		N/A	
Engineering contro	ıls	N/A	
		When handling leaking batteries. Wear	
		appropriate protective eyeglasses or chemical	
Eye protection		safely goggles as described by OSHA's eye and	
		face protection regulations in 29 CFR 1910.133 or	
		European Standard EN166.	
Skin protection		Use neoprene, rubber or nitrile gloves when	
		handing leaking batteries to prevent skin	
		exposure.	
Clothing		Wear appropriate protective clothing to minimize	
		contact with skin.	
Section 9 – Physical and Chemical Properties			
Appearance and odor		N/A	
PH		N/A	
Flash point(°C)		N/A	
Melting point (℃)		N/A	

Boiling point (℃)		N/A	
Relative density (water=1)		N/A	
Relative Vapour density (air=1)		N/A	
Vapour pressure (KPa)		N/A	
Heat of combustion (KJ/mol)		N/A	
Auto-ignition temperature (℃)		N/A	
Solubility		Insoluble in water	
Lower explosive limits % (V/V))		N/A	
Upper explosive limits % (V/V)		N/A	
	Section 1	10 – Stability and Reactivity	
Stability	Product is stable under storage conditions described in Section 7.		
La caraca a sella illiata	Change and distance and a solid.		

Upper explosive lin	nits % (V/V) N/A	
	Section 10 – Stability and Reactivity	
Stability	Product is stable under storage conditions described in Section 7.	
Incompatibilitie	Strong oxidizing agents, acids.	
S		
Conditions to	Direct sunlight, high temperature and high humidity.	
avoid	Do not heat above 60℃, incinerate, or expose contents to water.	
Hazardous	Will not occur.	
Polymerization		
Hazardous	When a battery is heated strongly by the surrounding fire, acrid or	
decomposition	harmful fume may be emitted.	
Section 11 – Toxicological Information		

None unless internal materials are exposed. Toxic information is available on the ingredients noted in section 2, but generally not available to intact batteries as used by customers.

In case of internal gas released or electrolyte spilled, electrolyte and organic solvents has small toxicity and may cause irritation of skin or eyes. Released gas may also cause irritation of skin of eyes.

Section	12 -	Ecologica	I Information
---------	------	------------------	---------------

Section 12 – Ecological Information		
Ecological toxicity	No data available.	
Environmental	Since a battery cell and the internal materials remain in the environment, it can't be degradable. Do not throw out into the environment.	
Bioaccumulation	No information	
Section 13 – Disposal Considerations		

	environment.	
Bioaccumulation	No information	
	Section 13 –Disposal Considerations	
Disposal measures	Do not throw out a used battery cell. Lithium ion cells and batteries can be disposable in accordance with appropriate federal, state and local regulations. However, we recommend recycling, since these cells and batteries contain recyclable material (LiFePO ₄).	
Section 14 – Transportation		

PROPER SHIPPING NAME:

Lithium-ion Battery (LiFePO4 Battery U3A1-50P-A)

LIN Number: 3480

Packing Group: II

Land transport (ADR/RID)

Class 9

Sea transport (IMDG) Class 9

Air transport (ICAO-TI/IATA DGR)

Class 9

National regulations:

National regulations for transport land GB 12268

This battery type is classified as dangerous goods for transport, because the watt-hour rating of the battery exceeds 100 Wh.

We also declare that this battery type meets the requirements of each test in the UN Manual of tests and Criteria Part III, Subsection 38.3 (ST/SG/AC.10/11/Rev.6)

Section 15 - Regulatory Information

Major applicable regulations for the transportation of lithium-ion cells and batteries are as follows:

The UN Model Regulations, United Nations ST/SG/AC.10/1/Rev 16. Recommendations on the Safe Transport of Dangerous Goods

The International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air Transport

The International Air Transport Association (IATA) Dangerous Goods Regulations (58 th Edition 2017)

International Maritime Organization (IMO) International Maritime Dangerous Goods Code (IMDG Code) Amdt. 37-14 2014

OSHA Hazard communication standard (29 CFR 1910.1200)

Hazardous V Non-hazard

Section 16 -Other Information

The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.

This safety data sheet provider guidance on health. Safety and environmental specs of the product and should not be construed as any guarantee of technical performance or

suitability for particular applications.

The material safety data sheet is furnished to every manufacturer as a reference to secure the safe handling of chemical. Every manufacturer is requested to carry out appropriate actions for chemical handling as their own responsibility. The supplier makes no warrantee, either express or implied. Concerning of this products. User assumes all risks resulting from its use.