



Product Service

Attestation of Conformity

No. T8A 070228 0099 Rev. 00

Holder of Certificate: **BYD CO LTD.**

Baolong Industrial Town, 1 Bao Ping Rd.
518116 Longgang, Shenzhen, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Batteries**
(Rechargeable Lithium-ion Battery System)

This Attestation of Conformity is issued on a voluntary basis in support of the Conformity Assessment Module A of Radio Equipment Directive 2014/53/EU. On the basis of the referenced test reports, the samples of the listed product were found to comply with the essential requirements of the above mentioned directive as implemented in the standards used valid at the time the tests were carried out. For the requirements of the Article(s) 3(2) and 3(3) only harmonized standards valid at the moment of issuing were used. The used standards completely cover all essential requirements of the Radio Equipment Directive applicable to this product. The manufacturer must ensure compliance of the manufactured products with the technical documentation and other requirements of the Radio Equipment Directive that apply to them. National legal requirements have to be considered before bringing the product to the market. See also notes overleaf.

Test report no.: 64771180331901

Date, 2018-11-09 (Tony Liu)

Page 1 of 2

After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives the manufacturer may sign a Declaration of Conformity and apply the CE-marking.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ♦ CERTIFICATE ♦ 認證證書 ♦ CERTIFICADO ♦ CERTIFICAT



Product Service

Attestation of Conformity

No. T8A 070228 0099 Rev. 00

Model(s):

Battery-Box L 3.5, Battery-Box L 7.0,
Battery-Box L 10.5, Battery-Box L 14.0

Parameters:

Norminal Voltage: 51.2VDC
Norminal Capacity: 70Ah (Battery-Box L 3.5)
140Ah (Battery-Box L 7.0)
210Ah (Battery-Box L 10.5)
280Ah (Battery-Box L 14.0)
Max. Current: 60A (Battery-Box L 3.5)
120A (Battery-Box L 7.0)
180A (Battery-Box L 10.5)
200A (Battery-Box L 14.0)

Test report No.:
64.771.18.03319.01R-RF
(EN 300 328 V2.1.1:2016, EN 62311:2008)
64.771.18.03319.01E-EMC
(Draft EN 301 489-1 V2.2.0:2017,
Draft EN 301 489-17 V3.2.0:2017,
EN 61000-6-1:2007, EN 61000-6-3 :2007/A1:2011)
64.290.18.03317.01-LVD
(EN 62477-1:2012/A11:2014)

Tested according to:

EN 300 328 V2.1.1:2016
Draft EN 301 489-1 V2.2.0:2017
Draft EN 301 489-17 V3.2.0:2017
EN 61000-6-1:2007
EN 61000-6-3:2007/A1:2011
EN 62477-1:2012/A11:2014
EN 62311:2008